	A T L	AS 159th DRIVE		
TEL 305.625.2451	TOLL FREE 80	0.762.7565	FAX 305.6	23.0475
www.atlasfooe	DSERV.COM	SALES@A	TLASFOODSEF	RV.COM

Project:	
Item No.:	
Quantity:	
2	

DROP-IN SERVING EQUIPMENT



ICE CHEST

□ WB-15 □ WB-19

Non-Mechanical

SPECIFICATIONS

TOP: Constructed of 18 gauge, type 304 stainless steel, die stamped with a raised perimeter bead. There shall be a solid vinyl gasket under the beaded edge to form a seal to the counter top, thus preventing seepage or marring of the counter top.

ICE CHEST: The inner liner shall be 22 gauge, type 304 stainless. All corners are coved with a minimum 1/4" radius. A 3/4" dia. threaded drain fitting is provided.

INSULATION: The pan is fully insulated with high density polystyrene, 1" thick on all sides, 1-1/2" thick on the bottom and enclosed with a 24 gauge galvanized steel outer liner.

LID: The ice chest is provided with a S/S double pan, insulated lid with a rubber, self-insulating hinge. The entire lid is removable.

Specifications subject to change without notice.

STANDARD FEATURES

- Fully insulated to hold ice longer
- Removable S/S hinged lid
- Factory applied gasket makes installation a snap and seals units to the counter top, thus eliminating seepage
- 1-Year Parts & Labor Warranty
- NSF Certified



MODEL	CUT-OUT	ICE CAPACITY	SHIP WT
	REQUIRED	(LBS.)	(LBS.)
WB-15	13-1/2" X 17-1/4"	40	34
	(34.2 X 43.8cm)	(18.1kg)	(15.4kg)
WB-19	17-1/4" X 22-1/4"	60	55
	(43.8 X 56.5cm)	(27.2kg)	(24.9kg)